



ROADSHINE

TRUCK & BUS RADIAL TYRES



RS601



- Suitable for steering wheel position of middle/long distance trucks on various road conditions.
- Unique tread groove design effectively expels stones from tire groove.
- 3 linear groove combine with steel ply provide excellent directional driving performance and prevents uneven tire wear.

Benefits



Vehicle



Size	Ply Rating	Spd	Load Index (single double)	Measure Rim (inch)	Max Load(kg)		Pressure(Kpa)		Inflated Dimensions		Tread Depth (mm)	Min. Dual Spacing(mm)
					Single	Dual	Single	Dual	SW	ODI		
7.50R16LT	14	L	122/118	6.00G	1500	1320	770	770	215	805	14.00	255
8.25R16LT	16	L	128/124	6.50H	1800	1600	770	770	235	855	14.50	278
9.00R20	16	K	144/142	7.00	2800	2650	900	900	259	1018	15.50	306
10.00R20	18	K	149/146	7.50	3250	3000	930	930	278	1055	16.50	328
11.00R20	18	K	152/149	8.00	3550	3250	930	930	293	1085	17.00	346
12.00R20	18	K	154/151	8.50	3750	3450	830	830	315	1125	17.50	372
12.00R20	20	K	156/153	8.50	4000	3650	900	900	315	1125	17.50	372
12.00R24	20	K	160/157	8.50	4500	4125	900	900	315	1222	17.50	372



RS602



- Suitable for all wheel position of middle/long-distance trucks on various road conditions.
- 3 zigzag grooves combine with lateral sipes on shoulder provides excellent traction and prevents hydroplaning.

Benefits



Long Haul



Longer Mileage



Powerful Traction

Vehicle



Size	Ply Rating	Spd	Load Index (single double)	Measure Rim (inch)	Max Load(kg) Single	Max Load(kg) Dual	Pressure(Kpa) Single	Pressure(Kpa) Dual	Inflated Dimensions SW	Inflated Dimensions ODI	Tread Depth (mm)	Min. Dual Spacing(mm)
7.00R16LT	14	M	118/114	5.50F	1320	1180	770	770	200	775	11.00	236
7.50R16LT	14	L	122/118	6.00G	1500	1320	770	770	215	805	14.00	255
8.25R16LT	16	L	128/124	6.50H	1800	1600	770	770	235	855	14.50	278
8.25R20	16	K	139/137	6.50	2430	2300	930	930	232	971	15.50	274
9.00R20	16	K	144/142	7.00	2800	2650	900	900	259	1018	15.50	306
10.00R20	18	K	149/146	7.50	3250	3000	930	930	278	1055	16.50	328
11.00R20	18	K	152/149	8.00	3550	3250	930	930	293	1085	17.00	346
11.00R22	16	K	152/149	8.00	3550	3250	830	830	293	1135	17.00	346
12.00R20	18	K	154/151	8.50	3750	3450	830	830	315	1125	18.00	372
12.00R20	20	K	156/153	8.50	4000	3650	900	900	315	1125	18.00	372
12.00R24	20	K	160/157	8.50	4500	4125	900	900	315	1222	17.50	372
11R22.5	16	L	146/143	8.25	3000	2725	830	830	279	1050	17.00	320
12R22.5	18	K	152/149	9.00	3550	3250	830	830	300	1084	17.00	343
13R22.5	18	L	154/151	9.75	3750	3450	830	830	320	1124	18.00	360
11R24.5	14	L	146/143	8.25	3000	2725	720	720	279	1104	17.00	318
11R24.5	16	L	149/146	8.25	3250	3000	830	830	279	1104	17.00	318
295/75R22.5	14	L	144/141	9.00	2800	2575	760	760	298	1014	17.00	335
295/75R22.5	16	L	146/143	9.00	3000	2725	830	830	298	1014	17.00	335
315/80R22.5	18	M	154/151	9.00	3750	3450	830	830	312	1076	17.00	351
315/80R22.5	20	K	157/154	9.00	4125	3750	900	900	312	1076	17.00	351
285/75R24.5	14	L	144/141	8.25	2800	2575	760	760	283	1050	17.00	318
285/75R24.5	16	L	147/144	8.25	3075	2800	830	830	283	1050	17.00	318

RS602A



- Suitable for all wheel position of middle/long-distance trucks on various road conditions.
- 3 zigzag grooves combine with lateral sipes on shoulder provides excellent traction and prevents hydroplaning.

Benefits



Long Haul




Longer Mileage



Powerful Traction

Vehicle



Size	Ply Rating	Spd	Load Index (single double)	Measure Rim (inch)	Max Load(kg)		Pressure(Kpa)		Inflated Dimensions		Tread Depth (mm)	Min. Dual Spacing(mm)
					Single	Dual	Single	Dual	SW	ODI		
7.50R16LT	14	L	122/118	6.00G	1500	1320	770	770	215	805	14.00	255
8.25R16LT	16	L	128/124	6.50H	1800	1600	770	770	235	855	14.50	278
9.00R20	16	K	144/142	7.00	2800	2650	900	900	259	1018	15.50	306
10.00R20	18	K	149/146	7.50	3250	3000	930	930	278	1055	16.50	328
11.00R20	18	K	152/149	8.00	3550	3250	930	930	293	1085	17.00	346
12.00R20	18	K	154/151	8.50	3750	3450	830	830	315	1125	18.00	372
315/80R22.5	18	M	154/151	9.00	3750	3450	830	830	312	1076	17.00	351

RS603



- Suitable for all wheel position of middle/long-distance buses and steering wheel position of trucks on good road conditions.
- 4 zigzag longitudinal grooves provides excellent directional driving performance.

Benefits



Long Haul



Longer Mileage



Comfort

Vehicle



Size	Ply Rating	Spd	Load Index (single double)	Measure Rim (inch)	Max Load(kg)		Pressure(Kpa)		Inflated Dimensions		Tread Depth (mm)	Min. Dual Spacing(mm)
					Single	Dual	Single	Dual	SW	ODI		
7.50R16LT	14	L	122/118	6.00G	1500	1320	770	770	215	805	14.00	255
8.25R16LT	16	L	128/124	6.50H	1800	1600	770	770	235	855	14.50	278
8.25R20	16	K	139/137	6.50	2430	2300	930	930	232	971	14.50	274
10.00R20	18	K	149/146	7.50	3250	3000	930	930	278	1055	17.00	328
11.00R20	18	K	152/149	8.00	3550	3250	930	930	293	1085	17.50	346
12.00R20	18	K	154/151	8.50	3750	3450	830	830	315	1125	17.50	372
11R22.5	16	L	146/143	8.25	3000	2725	830	830	279	1050	16.50	320

RS604



- Suitable for driving wheel position of middle/long distance trucks on various road conditions.
- Directional mixed pattern design provides extremely good traction and prevent hydroplaning.

Benefits



Long Haul



Powerful Traction

Vehicle



Size	Ply Rating	Spd	Load Index (single double)	Measure Rim (inch)	Max Load(kg)		Pressure(Kpa)		Inflated Dimensions		Tread Depth (mm)	Min. Dual Spacing(mm)
					Single	Dual	Single	Dual	SW	ODI		
7.00R16LT	14	M	118/114	5.50F	1320	1180	770	770	200	775	13.00	236
7.50R16LT	14	F	122/118	6.00G	1500	1320	770	770	215	805	14.00	255
8.25R16LT	16	F	128/124	6.50H	1800	1600	770	770	235	855	14.50	278
10.00R20	18	K	149/146	7.50	3250	3000	930	930	278	1055	18.00	328
11.00R20	18	K	152/149	8.00	3550	3250	930	930	293	1085	18.50	346
11.00R22	16	K	152/149	8.00	3550	3250	830	830	293	1135	18.50	346
12.00R20	18	K	154/151	8.50	3750	3450	830	830	315	1125	19.00	372
12.00R24	20	K	160/157	8.50	4500	4125	900	900	315	1222	18.00	372
8.5R17.5	12	L	121/120	6.00	1450	1400	620	620	215	802	15.00	242
9.5R17.5	16	L	132/130	6.75	2000	1900	850	850	240	842	17.00	270
215/75R17.5	16	M	127/124	6.00	1750	1600	830	830	211	767	16.00	237
235/75R17.5	16	M	132/129	6.75	2000	1850	830	830	233	797	16.00	262
225/80R17.5	16	L	123/122	6.75	1550	1500	750	750	203	803	16.00	255
8R19.5	14	L	128/126	6.00	1800	1700	890	890	208	856	15.00	234
225/70R19.5	14	L	128/126	6.75	1800	1700	760	760	226	811	16.00	254
245/70R19.5	16	M	135/133	7.50	2180	2060	830	830	248	839	16.00	279
265/70R19.5	16	J	143/141	7.50	2725	2575	860	860	262	867	16.00	295
11R22.5	16	LM	146/143	8.25	3000	2725	830	830	279	1050	16.50	320
12R22.5	18	M	152/149	9.00	3550	3250	830	830	300	1084	18.00	343
13R22.5	18	L	154/151	9.75	3750	3450	830	830	320	1124	18.00	360
295/80R22.5	16	M	150/147	9.00	3350	3075	830	830	298	1044	18.00	335
315/80R22.5	18	M	154/151	9.00	3750	3450	830	830	312	1076	18.00	351
315/80R22.5	20	K	157/154	9.00	4125	3750	900	900	312	1076	18.00	351
11R24.5	16	M	149/146	8.25	3250	3000	830	830	279	1104	18.00	318

RS605



- Suitable for all wheel positions of middle and long distance trucks on various road conditions.
- Special groove design effectively expels stone in groove bottom; avoiding damage to the groove.
- 3 longitudinal grooves combines with sipes effectively improves skid resistance.

Benefits



Long Haul




Powerful Traction



Comfort

Vehicle



Size	Ply Rating	Spd	Load Index (single double)	Measure Rim (inch)	Max Load(kg)		Pressure(Kpa)		Inflated Dimensions		Tread Depth (mm)	Min. Dual Spacing(mm)
					Single	Dual	Single	Dual	SW	ODI		
1100R20	18	K	152/149	8.00	3550	3250	930	930	293	1085	17.00	346

RS606



- Driving wheel position for construction site or on highway purpose.
- Unique sidewall design shows aggressive appearance and protects sidewall of tire from sharp impact.
- Dual tie-bar and wide foot print provide longer lasting tread life. Casing durability.
- Strong block design increases braking power and traction performance.

Benefits



Off Road



Powerful Traction



Mixed Surface

Vehicle



Size	Ply Rating	Spd	Load Index (single double)	Measure Rim (inch)	Max Load(kg)		Pressure(Kpa)		Inflated Dimensions		Tread Depth (mm)	Min. Dual Spacing(mm)
					Single	Dual	Single	Dual	SW	ODI		
9.00R20	16	F	144/142	7.00	2800	2650	900	900	259	1019	23.00	306
10.00R20	18	F	149/146	7.50	3250	3000	930	930	278	1055	23.00	328
11.00R20	18	F	152/149	8.00	3550	3250	930	930	293	1085	23.00	346
12.00R20	18	F	154/151	8.50	3750	3450	830	830	315	1125	23.00	372
12.00R24	20	F	160/157	8.50	4500	4125	900	900	315	1222	23.00	372
11R22.5	16	L	146/143	8.25	3000	2725	830	830	279	1050	23.00	320
12R22.5	18	F	152/149	9.00	3550	3250	830	830	300	1084	23.00	343
295/80R22.5	16	F	150/147	9.00	3350	3075	830	830	298	1044	21.00	335
315/80R22.5	18	F	154/151	9.00	3750	3450	830	830	312	1076	21.00	351
315/80R22.5	20	K	157/154	9.00	4125	3750	900	900	312	1076	21.00	351

RS607



- Suitable for all wheel position of middle/long distance buses and steering wheel position of trucks on good road conditions.
- 4 circumferential linear grooves combine with diamond-shaped tread blocks effectively enhance driving performance.
- 2 longitudinal narrow grooves on shoulder effectively reduces heat generation and prevents uneven tire wear.

Benefits




Long Haul



Comfort

Vehicle



Size	Ply Rating	Spd	Load Index (single double)	Measure Rim (inch)	Max Load(kg)		Pressure(Kpa)		Inflated Dimensions		Tread Depth (mm)	Min. Dual Spacing(mm)
					Single	Dual	Single	Dual	SW	ODI		
7.00R16LT	14	M	118/114	5.50F	1320	1180	770	770	200	775	11.50	236
10.00R20	18	K	149/146	7.50	3250	3000	930	930	278	1055	16.50	328
11R22.5	16	M	146/143	8.25	3000	2725	830	830	279	1050	15.00	320
12R22.5	18	M	152/149	9.00	3550	3250	830	830	300	1084	15.00	343
275/70R22.5	16	M	144/141	8.25	2800	2575	830	830	276	958	15.50	311
295/80R22.5	16	M	150/147	9.00	3350	3075	830	830	298	1044	15.00	335
315/80R22.5	18	M	154/151	9.00	3750	3450	830	830	312	1076	15.00	351
11R24.5	16	L	149/146	8.25	3250	3000	830	830	279	1104	16.00	318

RS608



- Suitable for driving position on paved road conditions. Suitable for middle and long haul usage on good road conditions.
- Special groove bottom design strengthens tire block and provides excellent self-cleaning ability.

Benefits



Long Haul



Longer Mileage



Comfort

Vehicle



Size	Ply Rating	Spd	Load Index (single double)	Measure Rim (inch)	Max Load(kg)		Pressure(Kpa)		Inflated Dimensions		Tread Depth (mm)	Min. Dual Spacing(mm)
					Single	Dual	Single	Dual	SW	ODI		
11R22.5	14	L	144/142	8.25	2800	2850	720	720	279	1050	23.00	320
11R22.5	16	L	146/143	8.25	3000	2725	830	830	279	1050	23.00	320
11R24.5	14	L	146/143	8.25	3000	2725	720	720	279	1104	23.00	318
11R24.5	16	L	149/146	8.25	3250	3000	830	830	279	1104	23.00	318
295/75R22.5	14	L	144/141	9.00	2800	2575	760	760	298	1014	23.00	335
295/75R22.5	16	M	146/143	9.00	3000	2725	830	830	298	1014	23.00	335
285/75R24.5	14	L	144/141	8.25	2800	2575	760	760	283	1050	23.00	318
285/75R24.5	16	L	147/144	8.25	3075	2800	830	830	283	1050	23.00	318

RS609



- Suitable for middle/long distance trucks on good road conditions.
- 5 zigzag-groove structure provides excellent traction and directional driving performance, as well as cornering stability.

Benefits



Long Haul



Longer Mileage



Comfort

Vehicle



Size	Ply Rating	Spd	Load Index (single double)	Measure Rim (inch)	Max Load(kg)		Pressure(Kpa)		Inflated Dimensions		Tread Depth (mm)	Min. Dual Spacing(mm)
					Single	Dual	Single	Dual	SW	ODI		
385/65R22.5	20	K	160	11.75	4500		900		389	1072	16.50	
385/65R22.5	22	K	162	11.75	4750		930		389	1072	16.50	
425/65R22.5	20	K	164	13.00	5000		830		430	1124	17.00	

RS610



- Deep and sturdy tread pattern for high mileage, stone & mud clearance. Stable center blocks minimize tread damage off road service.
- Optimum carcass construction for casing durability and uniform wear.

Benefits



Regional



Longer Mileage



Powerful Traction



Mixed Surface

Vehicle



Size	Ply Rating	Spd	Load Index (single double)	Measure Rim (Inch)	Max Load(kg)		Pressure(Kpa)		Inflated Dimensions		Tread Depth (mm)	Min. Dual Spacing(mm)
					Single	Dual	Single	Dual	SW	ODI		
7.50R16LT	14	L	122/118	6.00G	1500	1320	770	770	215	805	16.50	255
8.25R16LT	16	L	128/124	6.50H	1800	1600	770	770	235	855	16.00	278
9.00R20	16	K	144/142	7.00	2800	2650	900	900	259	1018	18.00	306
10.00R20	18	K	149/146	7.50	3250	3000	930	930	278	1055	19.00	328
11.00R20	18	K	152/149	8.00	3550	3250	930	930	293	1085	20.00	346
12.00R20	18	K	154/151	8.50	3750	3450	830	830	315	1125	21.00	372
11R22.5	16	M	146/143	8.25	3000	2725	830	830	279	1050	18.50	320
12R22.5	18	M	152/149	9.00	3550	3250	830	830	300	1084	22.00	343
295/80R22.5	16	M	150/147	9.00	3350	3075	830	830	298	1044	18.50	335
315/80R22.5	18	M	154/151	9.00	3750	3450	830	830	312	1076	18.50	351

RS611



- Suitable for driving wheel position of middle/long distance trucks on good road conditions.
- Unique tread groove design effectively expels stones from tire groove.
- 3 linear grooves combine with steel ply provide excellent direction driving performance and prevents uneven tire wear.

Benefits



Vehicle



Size	Ply Rating	Spd	Load Index (single double)	Measure Rim (inch)	Max Load(kg)		Pressure(Kpa)		Inflated Dimensions		Tread Depth (mm)	Min. Dual Spacing(mm)
					Single	Dual	Single	Dual	SW	ODI		
11R22.5	14	L	144/142	8.25	2800	2650	720	720	279	1050	21.00	320
11R22.5	16	L	146/143	8.25	3000	2725	830	830	279	1050	21.00	320
11R24.5	14	L	146/143	8.25	3000	2725	720	720	279	1104	21.00	318
11R24.5	16	L	149/146	8.25	3250	3000	830	830	279	1104	21.00	318
295/75R22.5	14	L	144/141	9.00	2800	2575	760	760	298	1014	21.00	335
295/75R22.5	16	M	146/143	9.00	3000	2725	830	830	298	1014	21.00	335
285/75R24.5	14	L	144/141	8.25	2800	2575	760	760	283	1050	21.00	318
285/75R24.5	16	L	147/144	8.25	3075	2800	830	830	283	1050	21.00	318

RS612



- Suitable for driving wheel position of middle/long distance trucks on various road conditions.
- Mixed groove pattern with open shoulder provides excellent traction, grip and anti-skid performance.

Benefits




Long Haul



Powerful Traction

Vehicle



Size	Ply Rating	Spd	Load Index (single double)	Measure Rim (inch)	Max Load(kg) Single Dual	Pressure(Kpa) Single Dual	Inflated Dimensions SW ODI		Tread Depth (mm)	Min. Dual Spacing(mm)
8.25R16LT	16	L	128/124	6.50H	1800 1800	770 770	235	855	15.50	278
9.00R20	16	K	144/142	7.00	2800 2850	900 900	259	1018	17.00	306
10.00R20	18	K	149/146	7.50	3250 3000	930 930	278	1055	17.00	328
11R22.5	16	M	146/143	8.25	3000 2725	830 830	279	1050	17.00	320
12R22.5	18	M	152/149	9.00	3550 3250	830 830	300	1084	17.00	343
13R22.5	18	K	154/151	9.75	3750 3450	830 830	320	1124	19.50	360
295/80R22.5	16	M	150/147	9.00	3350 3075	830 830	298	1044	17.00	335
315/70R22.5	18	M	151/148	9.00	3450 3150	830 830	312	1014	17.00	351
315/80R22.5	18	M	154/151	9.00	3750 3450	830 830	312	1076	17.00	351
315/80R22.5	20	K	157/154	9.00	4125 3750	900 900	312	1076	17.00	351

RS612A



- Suitable for driving wheel position of middle/long distance trucks on various road conditions.
- Mixed groove pattern with open shoulder provides excellent traction, grip and anti-skid performance.

Benefits



Long Haul



Powerful Traction

Vehicle



Size	Ply Rating	Spd	Load Index (single double)	Measure Rim (inch)	Max Load(kg)		Pressure(Kpa)		Inflated Dimensions		Tread Depth (mm)	Min. Dual Spacing(mm)
					Single	Dual	Single	Dual	SW	ODI		
8.25R16LT	16	L	128/124	6.50H	1800	1600	770	770	235	855	18.00	278
9.00R20	16	K	144/142	7.00	2800	2650	900	900	259	1018	19.00	306
10.00R20	18	K	149/146	7.50	3250	3000	930	930	278	1055	21.00	328
11R22.5	16	M	146/143	8.25	3000	2725	830	830	279	1050	21.00	320
12R22.5	18	M	152/149	9.00	3550	3250	830	830	300	1084	21.00	343
295/80R22.5	16	M	150/147	9.00	3350	3075	830	830	298	1044	21.00	335
315/70R22.5	18	M	152/148	9.00	3450	3150	830	830	312	1014	20.00	351
315/80R22.5	18	M	154/151	9.00	3750	3450	830	830	312	1076	21.00	351
315/80R22.5	20	K	157/154	9.00	4125	3750	900	900	312	1076	23.00	351

RS613



- Suitable for all wheel position of middle/long-distance buses and steering wheel position of trucks on good road conditions.
- 4 zigzag grooves combine with narrow lateral shoulder sipes provides excellent directional driving performance and prevent hydroplaning.

Benefits



Vehicle



Size	Ply Rating	Spd	Load Index (single double)	Measure Rim (inch)	Max Load(kg)		Pressure(Kpa)		Inflated Dimensions		Tread Depth (mm)	Min. Dual Spacing(mm)
					Single	Dual	Single	Dual	SW	ODI		
10R22.5	16	L	144/142	7.5	2800	2850	880	880	245	1020	15.00	290
12R22.5	18	M	152/149	9.00	3550	3150	830	830	300	1084	15.00	343
13R22.5	18	L	154/151	9.75	3750	3450	830	830	320	1124	17.00	360
275/70R22.5	16	M	144/141	8.25	2800	2575	830	830	276	958	15.00	311
295/80R22.5	16	M	150/147	9.00	3350	3075	830	830	298	1044	15.00	335
315/80R22.5	18	M	154/151	9.00	3750	3450	830	830	312	1076	15.00	351

RS614



- Suitable for all wheel position of middle/long-distance buses and steering wheel position of trucks on good road conditions.
- Unique groove design prevents stones from getting trapped in the tire grooves.
- Special shoulder design provides excellent protection from uneven tire wear.
- 4 linear grooves design provides excellent directional driving performance and prevent hydroplaning.

Benefits



Long Haul



Longer Mileage



Comfort

Vehicle



Size	Ply Rating	Spd	Load Index (single double)	Measure Rim (inch)	Max Load(kg)		Pressure(Kpa)		Inflated Dimensions		Tread Depth (mm)	Min. Dual Spacing(mm)
					Single	Dual	Single	Dual	SW	ODI		
255/70R22.5	16	L	140/137	7.50	2500	2300	830	830	255	930	15.00	287

RS615



- Suitable for all wheel position of middle/long-distance buses and steering wheel position of trucks on good road conditions.
- 4 linear grooves design provides excellent directional driving performance and prevent uneven tire wear.

Benefits



Long Haul




Longer Mileage



Comfort

Vehicle



Size	Ply Rating	Spd	Load Index (single double)	Measure Rim (inch)	Max Load(kg)		Pressure(Kpa)		Inflated Dimensions		Tread Depth (mm)	Min. Dual Spacing(mm)
					Single	Dual	Single	Dual	SW	ODI		
7.00R16LT	14	M	118/114	5.50F	1320	1180	730	730	200	775	11.00	236
8.5R17.5	12	L	121/120	6.00	1450	1400	620	620	215	802	13.00	242
9.5R17.5	16	L	132/130	6.75	2000	1900	850	850	240	842	13.00	270
215/75R17.5	16	M	127/124	6.00	1750	1600	830	830	211	767	14.00	237
225/80R17.5	16	L	123/122	6.75	1550	1500	750	750	203	803	12.00	255
235/75R17.5	16	M	132/129	6.75	2000	1850	830	830	233	797	14.00	262
8R19.5	14	L	128/126	6.00	1800	1700	890	890	208	856	13.00	234
225/70R19.5	14	L	128/126	6.75	1800	1700	760	760	228	811	14.00	254
245/70R19.5	16	M	135/133	7.50	2180	2060	830	830	248	839	14.00	279
265/70R19.5	16	J	143/141	7.50	2725	2575	860	860	262	867	14.00	295
8R22.5	12	L	128/126	6.00	1800	1700	760	760	208	936	13.00	234
9R22.5	14	L	136/134	6.75	2240	2120	830	830	230	970	14.00	262

RS616



- Direction tread design provides excellent high speed stability as well as maximum fuel efficiency.
 - Increased belt width enhances mileage and durability.
- Optimum block angle provides even wear.

Benefits



Vehicle



Size	Ply Rating	Spd	Load Index (single double)	Measure Rim (inch)	Max Load(kg) Single	Max Load(kg) Dual	Pressure(Kpa) Single	Pressure(Kpa) Dual	Inflated Dimensions		Tread Depth (mm)	Min. Dual Spacing(mm)
									SW	ODI		
14.00R20	20	G	164/161	10.00	5000	4625	790	790	375	1240	20.00	443

RS617



- Suitable for all wheel positions of earth mover or mine vehicle on hazard road and off road condition.
- Streamline pattern combine with rigid tread chunks provides excellent traction and driving performance.
- Reinforced tread block enhances its anti-rupture performance; effectively reducing cracks groove bottom, thereby resulting in a safer driving experience.

Benefits



Regional



Off Road



Powerful Traction



Anti-puncture

Vehicle



Size	Ply Rating	Spd	Load Index (single double)	Measure Rim (Inch)	Max Load(kg)		Pressure(Kpa)		Inflated Dimensions		Tread Depth (mm)	Min. Dual Spacing(mm)
					Single	Dual	Single	Dual	SW	ODI		
1000R20	18	F	149/146	7.50	3250	3000	930	930	278	1055	19.00	328
1100R20	18	F	152/149	8.00	3550	3250	930	930	293	1085	19.00	346
1200R20	18	F	154/151	8.50	3750	3450	830	830	315	1125	19.00	372
11R22.5	16	L	146/143	8.25	3000	2725	830	830	279	1050	19.00	320
12R22.5	18	K	152/149	9.00	3550	3250	830	830	300	1084	19.00	343
13R22.5	18	L	154/151	9.75	3750	3450	830	830	320	1124	19.00	360
295/80R22.5	16	M	150/147	9.00	3350	3075	830	830	298	1044	19.00	335
315/80R22.5	20	K	157/154	9.00	4125	3750	900	900	312	1076	19.00	351

RS617A



- Suitable for all wheel positions of earth mover or mine vehicle on hazard road and off road condition.
- Streamline pattern combine with rigid tread chunks provides excellent traction and driving performance.
- Reinforced tread block enhances its anti-rupture performance; effectively reducing cracks groove bottom, thereby resulting in a safer driving experience.

Benefits



Regional



Off Road



Powerful Traction



Anti-puncture

Vehicle



Size	Ply Rating	Spd	Load Index (single double)	Measure Rim (inch)	Max Load(kg)		Pressure(Kpa)		Inflated Dimensions		Tread Depth (mm)	Min. Dual Spacing(mm)
					Single	Dual	Single	Dual	SW	ODI		
1000R20	18	F	149/146	7.50	3250	3000	930	930	278	1055	23.00	328
1100R20	18	F	152/149	8.00	3550	3250	930	930	293	1085	23.00	346
1200R20	18	F	154/151	8.50	3750	3450	830	830	315	1125	23.00	372
11R22.5	16	J	146/143	8.25	3000	2725	830	830	279	1050	23.00	320
12R22.5	18	J	152/149	9.00	3550	3250	830	830	300	1084	23.00	343



RS618



- Suitable for all wheel position of middle/long distance buses and trailer wheel position of trucks on good road conditions.
- 4 linear tread grooves provides excellent directional driving performance and prevents uneven tire wear.

Benefits



Long Haul



Longer Mileage



Comfort

Vehicle



Size	Ply Rating	Spd	Load Index (single double)	Measure Rim (inch)	Max Load(kg)		Pressure(Kpa)		Inflated Dimensions		Tread Depth (mm)	Min. Dual Spacing(mm)
					Single	Dual	Single	Dual	SW	ODI		
11R22.5	14	L	144/142	8.25	2800	2850	720	720	279	1050	10.50	320
11R22.5	16	L	146/143	8.25	3000	2725	830	830	279	1050	10.50	320
11R24.5	14	L	146/143	8.25	3000	2725	720	720	279	1104	10.50	318
11R24.5	16	L	149/146	8.25	3250	3000	830	830	279	1104	10.50	318
295/75R22.5	14	L	144/141	9.00	2800	2575	760	760	298	1014	10.50	335
295/75R22.5	16	L	146/143	9.00	3000	2725	830	830	298	1014	10.50	335
285/75R24.5	14	L	144/141	8.25	2800	2575	760	760	283	1050	10.50	318
285/75R24.5	16	L	147/144	8.25	3075	2800	830	830	283	1050	10.50	318
315/80R22.5	20	K	157/154	9.00	4125	3750	900	900	312	1076	10.50	351



RS618A



- Suitable for all wheel position of middle/long distance buses and steering and trailer position wheel position of trucks on good road conditions.
- 4 linear tread grooves provides excellent directional driving performance and prevents uneven tire wear.
- Comfortable and safer driving experience, in addition to longer mileage.

Benefits



Long Haul



Longer Mileage



Comfort

Vehicle



Size	Ply Rating	Spd	Load Index (single double)	Measure Rim (inch)	Max Load(kg)		Pressure(Kpa)		Inflated Dimensions		Tread Depth (mm)	Min. Dual Spacing(mm)
					Single	Dual	Single	Dual	SW	ODI		
7.50R16LT	14	L	122/118	6.00G	1500	1320	770	770	215	805	14.00	255
8.25R16LT	16	L	128/124	6.50H	1800	1600	770	770	235	855	14.50	278
8.25R20	16	K	139/137	6.50	2430	2300	930	930	232	971	15.50	274
9.00R20	16	K	144/142	7.00	2800	2650	900	900	259	1018	16.50	306
10.00R20	18	K	149/146	7.50	3250	3000	930	930	278	1055	17.50	328
11.00R20	18	K	152/149	8.00	3550	3250	930	930	293	1085	17.50	346
11R22.5	14	L	144/142	8.25	2800	2650	720	720	279	1050	16.50	320
11R22.5	16	L	146/143	8.25	3000	2725	830	830	279	1050	16.50	320
11R24.5	14	L	146/143	8.25	3000	2725	720	720	279	1104	16.50	318
11R24.5	16	L	149/146	8.25	3250	3000	830	830	279	1104	16.50	318
255/70R22.5	16	L	140/137	7.50	2500	2300	830	830	255	930	14.50	287
295/75R22.5	14	L	144/141	9.00	2800	2575	760	760	298	1014	16.50	335
295/75R22.5	16	L	146/143	9.00	3000	2725	830	830	298	1014	16.50	335
285/75R24.5	14	L	144/141	8.25	2800	2575	760	760	283	1050	16.50	318
285/75R24.5	16	L	147/144	8.25	3075	2800	830	830	283	1050	16.50	318
315/80R22.5	20	K	157/154	9.00	4125	3750	900	900	312	1076	19.00	351

RS619



- Suitable for tipper trucks on tough road conditions such as mine and construction site.
- Streamline pattern combine with rigid tread chunks provide excellent traction and driving performance.
- Deeper tread pattern design offers enhanced tire mileage for better economy.
- Reinforced tread block enhances its anti-rupture performance; effectively reducing cracks in groove bottom thereby resulting in a safer driving experience.

Benefits



Regional



Longer Mileage




Powerful Traction



Mixed Surface

Vehicle



Size	Ply Rating	Spd	Load Index (single double)	Measure Rim (Inch)	Max Load(kg)		Pressure(Kpa)		Inflated Dimensions		Tread Depth (mm)	Min. Dual Spacing(mm)
					Single	Dual	Single	Dual	SW	ODI		
9.00R20	16	F	144/142	7.00	2800	2650	900	900	259	1018	18.50	306
10.00R20	18	F	149/146	7.50	3250	3000	930	930	278	1055	19.00	328
11.00R20	18	F	152/149	8.00	3550	3250	930	930	293	1085	21.00	346
12.00R20	18	F	154/151	8.50	3750	3450	830	830	315	1125	21.00	372

RS619A



- Suitable for tipper trucks on tough road conditions such as mine and construction site.
- Streamline pattern combine with rigid tread chunks provide excellent traction and driving performance.
- Deeper tread pattern design offers enhanced tire mileage for better economy.
- Reinforced tread block enhances its anti-rupture performance; effectively reducing cracks in groove bottom thereby resulting in a safer driving experience.

Benefits



Regional



Longer Mileage




Powerful Traction



Mixed Surface

Vehicle



Size	Ply Rating	Spd	Load Index (single double)	Measure Rim (Inch)	Max Load(kg)		Pressure(Kpa)		Inflated Dimensions		Tread Depth (mm)	Min. Dual Spacing(mm)
					Single	Dual	Single	Dual	SW	ODI		
9.00R20	16	F	144/142	7.00	2800	2650	900	900	259	1018	18.50	306
10.00R20	18	F	149/146	7.50	3250	3000	930	930	278	1055	19.00	328
11.00R20	18	F	152/149	8.00	3550	3250	930	930	293	1085	21.00	346
12.00R20	18	F	154/151	8.50	3750	3450	830	830	315	1125	21.00	372

RS620



- Suitable for all wheel positions of middle and long distance coach, steering wheel position of middle and long distance trucks.
- Specially designed for long distance transportation vehicles on good road conditions.
- Comfortable and safer driving experience, In addition to longer mileage.

Benefits



Vehicle



Size	Ply Rating	Spd	Load Index (single double)	Measure Rim (inch)	Max Load(kg)		Pressure(Kpa)		Inflated Dimensions		Tread Depth (mm)	Min. Dual Spacing(mm)
					Single	Dual	Single	Dual	SW	ODI		
205/75R17.5	14	M	124/122	6.00	1600	1500	750	750	204	752	13.50	
11R22.5	16	M	146/143	8.25	3000	2725	830	830	279	1050	15.00	320
12R22.5	18	M	152/149	9.00	3550	3250	830	830	300	1084	15.00	343
275/80R22.5	16	M	149/146	8.25	3250	3000	850	850	276	1012	15.50	311
295/75R22.5	16	M	144/141	9.00	2800	2575	830	830	298	1014	16.00	335
295/80R22.5	16	M	150/147	9.00	3350	3075	830	830	298	1044	15.00	335
315/70R22.5	18	L	151/148	9.00	3450	3150	830	830	312	1014	15.00	351
315/80R22.5	18	M	154/151	9.00	3750	3450	830	830	312	1076	15.00	351
315/80R22.5	20	K	157/154	9.00	4125	3750	830	830	312	1076	15.00	351
385/65R22.5	20	K	160	11.75	4500		900		389	1072	16.50	
11R24.5	16	M	149/146	8.25	3250	3000	830	830	279	1104	15.00	318
285/75R24.5	16	L	147/144	8.25	3075	2800	830	830	283	1050	15.00	318

RS620A



- Suitable for all wheel positions of middle/long distance buses and steering wheel position of trucks on good road conditions.
- Unique groove design prevents stones from getting trapped in the tire grooves.
- Special shoulder design provides excellent protection from uneven tire wear.
- 4 linear grooves design provides excellent directional driving performance and prevents hydroplaning.

Benefits



Vehicle



Size	Ply Rating	Spd	Load Index (single double)	Measure Rim (inch)	Max Load(kg) Single Dual	Pressure(Kpa) Single Dual	Inflated Dimensions SW ODI		Tread Depth (mm)	Min. Dual Spacing(mm)
7.50R16LT	14	L	122/118	6.00G	1500 1320	770 770	215	805	13.00	255
8.25R16LT	16	L	128/124	6.50H	1800 1600	770 770	235	855	14.50	278
295/60R22.5	16	M	150/147	9.00	3350 3075	830 830	298	1044	15.50	335

RS621



- Suitable for short haul and low-speed trucks on poor road conditions.
- Streamline pattern combine with rigid tread chunks provide excellent traction and driving performance.
- Deeper tread pattern design offers enhance tire mileage for better economy.

Benefits



Regional



Longer Mileage



Powerful Traction



Anti-chipping

Vehicle



Size	Ply Rating	Spd	Load Index (single double)	Measure Rim (inch)	Max Load(kg)		Pressure(Kpa)		Inflated Dimensions		Tread Depth (mm)	Min. Dual Spacing(mm)
					Single	Dual	Single	Dual	SW	ODI		
10.00R20	18	F	149/146	7.50	3250	3000	930	930	278	1055	22.00	328
11.00R20	18	F	152/149	8.00	3550	3250	930	930	293	1085	23.00	346
12.00R20	18	F	154/151	8.50	3750	3450	830	830	315	1125	24.00	372
295/80R22.5	16	M	150/147	9.00	3350	3075	830	830	298	1044	23.00	335

RS622



- Suitable for driving wheel position of vans on various road conditions.
- Streamline pattern combine with rigid tread chunks provide excellent traction and driving performance.
- Deeper tread pattern design offers enhanced tire mileage for better economy.
- Reinforced tread block enhances its anti-rupture performance; effectively reducing cracks in groove bottom, thereby resulting in a safer driving experience.

Benefits



Vehicle



Size	Ply Rating	Spd	Load Index (single double)	Measure Rim (inch)	Max Load(kg)		Pressure(Kpa)		Inflated Dimensions		Tread Depth (mm)	Min. Dual Spacing(mm)
					Single	Dual	Single	Dual	SW	ODI		
7.50R16LT	14	K	122/118	6.00G	1500	1320	770	770	215	805	14.00	255
8.25R16LT	16	K	128/124	6.50H	1800	1600	770	770	235	855	16.00	278
8.25R20	16	K	139/137	6.50	2430	2300	930	930	232	971	17.50	274
9.00R20	16	K	144/142	7.00	2800	2650	900	900	259	1018	19.00	306
10.00R20	18	K	149/146	7.50	3250	3000	930	930	278	1055	21.00	328
11.00R20	18	K	152/149	8.00	3550	3250	930	930	293	1085	21.00	346
12.00R20	18	K	154/151	8.50	3750	3450	830	830	315	1125	21.50	372
12.00R20	20	G	156/153	8.50	4000	3650	900	900	315	1125	21.50	372
11R22.5	16	F	148/145	8.25	3150	2900	850	850	279	1050	20.00	320
12R22.5	18	M	152/149	9.00	3550	3250	830	830	300	1084	20.00	343
13R22.5	18	L	154/151	9.75	3750	3450	830	830	320	1124	20.00	360
295/80R22.5	16	M	150/147	9.00	3350	3075	830	830	298	1044	20.00	335
315/80R22.5	18	F	154/151	9.00	3750	3450	830	830	312	1076	21.00	351

RS623



- On normal road conditions.
- Middle-to-long haul for truck.
- All position.
- Excellent wear resistant, Durability, Economy.

Benefits



Long Haul




Longer Mileage



Powerful Traction

Vehicle



Size	Ply Rating	Spd	Load Index (single double)	Measure Rim (inch)	Max Load(kg)		Pressure(Kpa)		Inflated Dimensions		Tread Depth (mm)	Min. Dual Spacing(mm)
					Single	Dual	Single	Dual	SW	ODI		
7.50R16LT	14	L	122/118	6.00G	1500	1320	770	770	215	805	14.00	255
8.25R16LT	16	L	128/124	6.50H	1800	1600	770	770	235	855	16.00	278
9.00R20	16	K	144/142	7.00	2800	2650	900	900	259	1018	19.00	306
10.00R20	18	K	149/146	7.50	3250	3000	930	930	278	1055	21.00	328
11.00R20	18	K	152/149	8.00	3550	3250	930	930	293	1085	21.00	346
12.00R20	18	K	154/151	8.50	3750	3450	830	830	315	1125	21.50	372
11R22.5	16	M	146/143	8.25	3000	2725	830	830	279	1050	18.00	320
12R22.5	18	M	152/149	9.00	3550	3250	830	830	300	1084	18.00	343
295/80R22.5	16	M	150/147	9.00	3350	3075	830	830	298	1044	17.50	335
315/80R22.5	18	M	154/151	9.00	3750	3450	830	830	312	1076	18.50	351
315/80R22.5	20	K	157/154	9.00	4125	3750	900	900	312	1076	19.00	351

RS625



- Suitable for all wheel positions of middle/long distance buses and steering wheel position of trucks on good road conditions.
- 3 linear grooves design provides excellent directional driving performance and withstand uneven tire wear.

Benefits



Vehicle



Size	Ply Rating	Spd	Load Index (single double)	Measure Rim (inch)	Max Load(kg)		Pressure(Kpa)		Inflated Dimensions		Tread Depth (mm)	Min. Dual Spacing(mm)
					Single	Dual	Single	Dual	SW	ODI		
12.00R24	20	K	160/157	8.50	4500	4125	900	900	312	1222	19.50	372
11R22.5	16	M	146/143	8.25	3000	2725	830	830	279	1050	16.50	320
12R22.5	18	M	152/149	9.00	3550	3250	830	830	300	1084	16.50	343
295/80R22.5	16	M	150/147	9.00	3350	3075	830	830	298	1044	16.50	335
315/80R22.5	18	M	154/151	9.00	3750	3450	830	830	312	1076	17.00	351
315/80R22.5	20	K	157/154	9.00	4125	3750	900	900	312	1076	17.00	351

RS626



- Suitable for driving wheel position of middle/long distance trucks on various road conditions.
- Mixed pattern tread combine with open shoulder design effectively reduce heat generation on shoulder.

Benefits



Long Haul



Longer Mileage



Powerful Traction

Vehicle



Size	Ply Rating	Spd	Load Index (single double)	Measure Rim (inch)	Max Load(kg)		Pressure(Kpa)		Inflated Dimensions		Tread Depth (mm)	Min. Dual Spacing(mm)
					Single	Dual	Single	Dual	SW	ODI		
11R22.5	16	M	146/143	8.25	3000	2725	830	830	279	1050	18.00	320
12R22.5	18	K	152/149	9.00	3550	3250	830	830	300	1084	18.00	343
13R22.5	18	L	154/151	9.75	3750	3450	830	830	320	1124	18.00	360
295/80R22.5	16	M	150/147	9.00	3350	3075	830	830	298	1044	18.00	335
315/80R22.5	18	M	154/151	9.00	3750	3450	830	830	312	1076	18.50	351
315/80R22.5	20	K	157/154	9.00	4125	3750	900	900	312	1076	18.50	351

RS627



- Suitable for all wheel positions of middle/long-distance buses and steering wheel position of trucks on good road conditions.
- 4 linear grooves design provides excellent directional driving performance and prevents uneven tire wear.

Benefits



Vehicle



Size	Ply Rating	Spd	Load Index (single double)	Measure Rim (Inch)	Max Load(kg)		Pressure(Kpa)		Inflated Dimensions		Tread Depth (mm)	Min. Dual Spacing(mm)
					Single	Dual	Single	Dual	SW	ODI		
11R22.5	16	M	146/143	8.25	3000	2725	830	830	279	1050	15.50	320
12R22.5	18	K	152/149	9.00	3550	3250	830	830	300	1084	15.50	343
13R22.5	18	L	154/151	9.75	3750	3450	830	830	320	1124	15.50	360
295/80R22.5	16	M	150/147	9.00	3350	3075	830	830	298	1044	15.50	335
315/80R22.5	20	K	157/154	9.00	4125	3750	900	900	312	1076	15.50	351
385/65R22.5	20	K	160	11.75	4500		900		389	1072	16.50	

RS628



- Regional haul on & off Road.
- Truck all position.
- Excellent durability under loading.
- Wear resistance.

Benefits



Long Haul



Longer Mileage



Mixed Surface




Regional



Powerful Traction

Vehicle



Size	Ply Rating	Spd	Load Index (single double)	Measure Rim (inch)	Max Load(kg)		Pressure(Kpa)		Inflated Dimensions		Tread Depth (mm)	Min. Dual Spacing(mm)
					Single	Dual	Single	Dual	SW	ODI		
7.00R16LT	14	L	118/114	5.50F	1320	1180	770	770	200	775	13.00	236
7.50R16LT	14	M	122/118	6.00G	1500	1320	770	770	215	805	14.00	255
8.25R16LT	16	L	128/124	6.50H	1800	1600	770	770	235	855	14.50	278
8.25R20	16	K	139/137	6.50	2430	2300	930	930	232	971	15.50	274
9.00R20	16	K	144/142	7.00	2800	2650	900	900	259	1018	15.50	306
10.00R20	18	K	149/146	7.50	3250	3000	930	930	278	1055	16.50	328
11.00R20	18	K	152/149	8.00	3550	3250	930	930	293	1085	17.00	346
12.00R20	18	K	154/151	8.50	3750	3450	830	830	315	1125	18.00	372
12R22.5	18	M	152/149	9.00	3550	3250	830	830	300	1084	18.00	343

RS629



- Suitable for all wheel position of middle/long-distance buses and steering wheel position of trucks on good road conditions.
- Unique groove design prevents stones from getting trapped in the tire grooves.
- Special shoulder design provides excellent protection from uneven tire wear.
- 4 linear groove design provide excellent directional driving performance and prevent hydroplaning .

Benefits



Vehicle



Size	Ply Rating	Spd	Load Index (single double)	Measure Rim (inch)	Max Load(kg)		Pressure(Kpa)		Inflated Dimensions		Tread Depth (mm)	Min. Dual Spacing(mm)
					Single	Dual	Single	Dual	SW	ODI		
11R22.5	16	M	146/143	8.25	3000	2725	830	830	279	1050	15.50	320
12R22.5	18	K	152/149	9.00	3550	3250	830	830	300	1084	15.50	343
295/80R22.5	16	M	150/147	9.00	3350	3075	830	830	298	1044	15.50	335
315/80R22.5	20	K	157/154	9.00	4125	3750	900	900	312	1076	15.50	351

RS630



- Unique groove design prevents stones from getting trapped in the tire grooves.
- Special shoulder design provides excellent protection from uneven tire wear.
- Suitable for all wheel position of middle/long-distance buses and steering wheel position of trucks on good road conditions.

Benefits



Vehicle



Size	Ply Rating	Spd	Load Index (single double)	Measure Rim (inch)	Max Load(kg)		Pressure(Kpa)		Inflated Dimensions		Tread Depth (mm)	Min. Dual Spacing(mm)
					Single	Dual	Single	Dual	SW	ODI		
12.00R20	18	K	154/151	8.50	3750	3450	830	830	315	1125	18.00	372
12.00R24	20	K	160/157	8.50	4500	4125	900	900	315	1222	18.00	372

RS631



- Suitable for middle/long distance on good road conditions.
- 5 zigzag-groove structure provides excellent traction and directional driving performance, as well as cornering stability.

Benefits



Long Haul




Longer Mileage



Comfort

Vehicle



Size	Ply Rating	Spd	Load Index (single double)	Measure Rim (Inch)	Max Load(kg)		Pressure(Kpa)		Inflated Dimensions		Tread Depth (mm)	Min. Dual Spacing(mm)
					Single	Dual	Single	Dual	SW	ODI		
385/65R22.5	20	K	160	11.75	4500		900		389	1072	16.50	
425/65R22.5	20	K	164	13.00	5000		830		430	1124	17.00	

RS631+



- New low heat tire shoulder designed to provide excellent high-speed performance.
- Widen tread design effectively increases the wear volume and extend tire life.
- Unique tire shape and strong steel cord structure providing excellent durability performance.

Benefits



Long Haul



Powerful Traction



Comfort

Vehicle



Size	Ply Rating	Spd	Load Index (single double)	Measure Rim (Inch)	Max Load(kg)		Pressure(Kpa)		Inflated Dimensions		Tread Depth (mm)	Min. Dual Spacing(mm)
					Single	Dual	Single	Dual	SW	ODI		
385/65R22.5	20	K	160	11.75	4500		900		389	1072	16.50	

RS632



- Suitable for all wheel positions of earth mover or mine vehicle on hazard road and off road condition.
- Reinforced tread block enhances its anti-rupture performance; effectively reducing cracks groove bottom, thereby resulting in a safer driving experience.

Benefits



Regional



Off Road



Powerful Traction



Anti-puncture

Vehicle



Size	Ply Rating	Spd	Load Index (single double)	Measure Rim (inch)	Max Load(kg)		Pressure(Kpa)		Inflated Dimensions		Tread Depth (mm)	Min. Dual Spacing(mm)
					Single	Dual	Single	Dual	SW	ODI		
7.50R16LT	14	L	122/118	6.00G	1500	1320	770	770	215	805	14.00	255
8.25R16LT	16	L	128/124	6.50H	1800	1600	770	770	235	855	14.50	278
10.00R20	18	K	149/146	7.50	3250	3000	930	930	278	1055	16.50	328
11.00R20	18	K	152/149	8.00	3550	3250	930	930	293	1085	17.00	346
12.00R20	18	K	154/151	8.50	3750	3450	830	830	315	1125	18.00	372
13.00R25NHSTT		A2	182	10.00/1.5	8500		950		345	1302	26.00	
13.00R25NHSTT		B	182	10.00/1.5	8500		950		345	1302	26.00	

RS634



- Special design for anti-skidding and perfect handling.
- Central tread ensure excellent gripping and reduce rolling resistance.
- Unique technical formula improve the wear-resistance and stability..
- Suitable for middle/long distance on good road conditions.
- 4 zigzag-groove structure provides excellent traction and directional driving performance, as well as cornering stability.

Benefits



Long Haul




Longer Mileage



Comfort

Vehicle



Size	Ply Rating	Spd	Load Index (single double)	Measure Rim (inch)	Max Load(kg)		Pressure(Kpa)		Inflated Dimensions		Tread Depth (mm)	Min. Dual Spacing(mm)
					Single	Dual	Single	Dual	SW	ODI		
11R22.5	14	L	144/142	8.25	2800	2650	720	720	279	1050	10.50	320
11R22.5	16	L	146/143	8.25	3000	2725	830	830	279	1050	10.50	320
11R24.5	14	L	146/143	8.25	3000	2725	720	720	279	1104	10.50	318
11R24.5	16	L	149/146	8.25	3250	3000	830	830	279	1104	10.50	318
285/75R24.5	14	M	144/141	8.25	2800	2575	760	760	283	1050	10.50	318
285/75R24.5	16	L	147/144	8.25	3075	2800	830	830	283	1050	10.50	318

RS635



- Safe and advance pattern design reduce rolling resistance and ensure tire fuel economy and high speed performance.
- Suitable for steering wheel position of middle/long distance trucks on good road conditions.
- Unique tread groove design effectively expels stones from tire groove.
- 5 linear grooves combine with steel ply provide excellent direction driving performance and prevents uneven tire wear.

Benefits



Vehicle



Size	Ply Rating	Spd	Load Index (single double)	Measure Rim (inch)	Max Load(kg)		Pressure(Kpa)		Inflated Dimensions		Tread Depth (mm)	Min. Dual Spacing(mm)
					Single	Dual	Single	Dual	SW	ODI		
11R22.5	14	L	144/142	8.25	2800	2650	720	720	279	1050	16.50	320
11R22.5	16	L	146/143	8.25	3000	2725	830	830	279	1050	16.50	320
11R24.5	14	L	146/143	8.25	3000	2725	720	720	279	1104	16.50	318
11R24.5	16	L	149/146	8.25	3250	3000	830	830	279	1104	16.50	318
285/75R24.5	14	M	144/141	8.25	2800	2575	760	760	283	1050	16.50	318
285/75R24.5	16	L	147/144	8.25	3075	2800	830	830	283	1050	16.50	318

RS637



- Suitable for drive positions.
- Mixed deep tread block, widened tread, increased grip performance.
- Design for on all types of non-paved roads.

Benefits



Vehicle



Size	Ply Rating	Spd	Load Index (single double)	Measure Rim (inch)	Max Load(kg) Single Dual	Pressure(Kpa) Single Dual	Inflated Dimensions SW ODI	Tread Depth (mm)	Min. Dual Spacing(mm)
315/80R22.5	20	K	157/154	9.00	4125 3750	900 900	312 1076	23.00	351

HONGTYRE GLOBAL CO., LIMITED

Add: NO.43 Bangkok Road, Qingdao Free Trade Zone, Qingdao, China.

Tel: +86-532- 86766013, +86-532- 86768126,

+86-532- 86768852, +86-532- 86766033,

+86-532- 86768057, +86-532- 86768067,

+86-532- 86768860 +86-532- 86768065

Fax: +86-532-86769930

Email: roadshine@hongtyre.com;

Web: www.hongtyre.com